

# MATERIAL SAFETY DATA SHEET

## Special Industrial Solvent Formula C-2 200 proof

This MSDS is valid for all grades and catalog #'s

### 1. IDENTIFICATION OF SUBSTANCE / MIXTURE AND OF SUPPLIER

**Product Identifier:** Denatured Ethanol  
**Synonyms:** Denatured Alcohol; SIS-2, SIC-2; Special Insolv C-2 200 Proof; Ethanol denatured with Isopropanol & MIBK  
**Other means of identification:** Not available

#### Recommended use of the chemical and restrictions on use:

Special industrial solvents are intended for use as ingredients or solvents in manufacturing processes and shall not be distributed through retail channels for sale as consumer commodities for personal or household use. When a special industrial solvent is used in the manufacture of an article for sale, sufficient ingredients shall be added to definitely change the composition and character of the special industrial solvent. A special industrial solvent shall not be reprocessed into another solvent intended for sale if the other solvent would contain more than 50% alcohol by volume.

#### Supplier Details:

**Pharmco Products, Inc.**  
1101 Isaac Shelby Drive, Shelbyville,  
KY 40065, USA.  
Tel: 502.232.7600  
Fax: 502.633.6100  
CCN17213

**Pharmco Products, Inc.**  
58 Vale Road, Brookfield,  
CT 06804, USA.  
Tel: 203.740.3471  
Fax: 203.740.3481  
CCN17213



**Emergency Contact:** CHEMTREC: 1.800.424.9300 (USA) / +1.703.527.3887 (International)

### 2. HAZARDS IDENTIFICATION

#### Emergency Overview:

This material is considered hazardous in accordance to OSHA hazardous Communication guidelines. Material is flammable and can burn with little to no visible flame.

#### OSHA Hazards:


Flammable liquid, Target Organ Effect, Irritant

#### Target Organs:

Cardiovascular system, Central nervous system, Gastrointestinal tract, Kidney, Liver

Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)  
+1.703.527.3887 (INT)

**NFPA**



**GHS label elements, including precautionary statements**



**Signal Word:**

DANGER!

**Hazard statement(s)**

H225	Highly flammable liquid and vapor.
H315	Causes skin irritation.
H320	Causes eye irritation
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

**Precautionary statement(s)**

P501	Dispose of contents and container to an approved waste disposal plant.
P240	Ground/bond container and receiving equipment.
P337 + P313	If eye irritation persists: Get medical attention.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention.
P303 + P361 + P353	IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P210	Keep away from heat, sparks, open flames, and hot surfaces. No smoking.
P233	Keep container tightly closed.

**Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)  
+1.703.527.3887 (INT)**

P403 + P235	Store in a well-ventilated place. Keep cool.
P243	Take precautionary measures against static discharge.
P241	Use explosion-proof electrical, ventilating, and lighting equipment.
P242	Use only non-sparking tools.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves and eye and face protection.

**GHS Classification(s)**

Eye irritation (Category 2B)  
Flammable Liquids (Category 2)  
Skin irritation (Category 2)  
Specific target organ toxicity - single exposure (Category 3)

**Other hazards which do not result in classification:**

**Potential Health Effects:**

Organ	Description
Eyes	Can cause eye irritation such as stinging, tearing, and redness.
Ingestion	Ingestion can cause dizziness, faintness, drowsiness decreased awareness or responsiveness, nausea, vomiting, staggering gait, lack of coordination, coma and death.
Inhalation	High vapor concentration can cause burning sensation in nose and throat and stinging and watering in the eyes. At concentrations which cause irritation, dizziness, faintness, drowsiness, nausea and vomiting can also occur.
Skin	Can cause irritation to the skin. Prolonged or repeated contact may cause defatting and drying of the skin.
Chronic	Long term repeated oral exposure to ethanol may result in the development of progressive liver injury with fibrosis.

**3. COMPOSITION AND INFORMATION ON INGREDIENTS**

**Chemical identity:** Special Industrial Solvent Formula C-2 200 Proof  
**Common name / Synonym:** Denatured Alcohol;SIS-2, SIC-2; Special Insolv C-2 200 Proof; Ethanol denatured with Isopropanol & MIBK  
**UN #:** 1987

% Volume	Material	CAS
89.95	Ethanol	64-17-5
9.10	Isopropyl Alcohol	67-63-0
0.95	Methyl Isobutyl Ketone	108-10-1

**4. FIRST AID MEASURES**

**General advice**

**Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)  
+1.703.527.3887 (INT)**

Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### **Skin**

Wash skin with soap and copious amounts of water. Seek medical attention.

#### **Inhalation**

Remove person to fresh air. If signs/symptoms continue, get medical attention. Give oxygen or artificial respiration as needed.

#### **Eyes**

Thoroughly flush the eyes with large amounts of clean low-pressure water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Seek medical attention.

#### **Ingestion**

DO NOT induce vomiting. If vomiting does occur, have victim lean forward to prevent aspiration. Rinse mouth with water. Seek medical attention. Never give anything by mouth to an unconscious individual.

#### **Note to Physician**

Symptoms will vary with alcohol level of the blood. Mild alcohol intoxication occurs at blood levels between 0.05-0.15%. Approximately 25% of individuals show signs of intoxication at these levels. Above 0.15% the person is definitely under the influence of ethanol; 50-95% of individuals are clinically intoxicated at these levels. Severe poisoning occurs when the blood is ethanol level is 0.3- 0.5%. Above 0.5% the individual will be comatose and death can occur. The unabsorbed ethanol should be removed by gastric lavage after intubating the patient to prevent aspiration. Avoid the use of depressant drugs and administering excessive amounts of fluids.

---

## **5. FIRE FIGHTING MEASURES**

#### **Suitable (and unsuitable) extinguishing media:**

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

#### **Specific hazards arising from the chemical (e.g., nature of any hazardous combustion products):**

Carbon oxides expected to be the primary hazardous combustion product.

#### **Special protective equipment and precautions for firefighters:**

Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Keep unopened containers cool by spraying with water.

#### **Unusual Fire and Explosion Hazards:**

- May produce a floating fire hazard.
- Static ignition hazard can result from handling and use.
- Vapors may travel to source of ignition and flash back.
- Vapors may settle in low or confined spaces.

**Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)  
+1.703.527.3887 (INT)**

Alcohols burn with a pale blue flame which may be extremely hard to see under normal lighting conditions. Personnel may only be able to feel the heat of the fire without seeing flames. Extreme caution must be exercised in fighting alcohol fires. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire.

#### **Flammable Properties**

##### **Classification**

OSHA/NFPA Class IB Flammable Liquid.

##### **Flash point**

14°C (58°F) - closed cup

##### **Autoignition temperature**

363°C (685.4°F) - (Ethyl Alcohol)

---

## **6. ACCIDENTAL RELEASE MEASURES**

### **Personal precautions, protective equipment and emergency procedures:**

Do not inhale vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

### **Environmental precautions:**

Stop leak. Contain spill if possible and safe to do so. Prevent product from entering drains.

### **Methods and materials for containment and cleaning up:**

Contain spill, then collect with an electrically protected vacuum cleaner or by wet-brushing and put the material into a convenient waste disposal container. Keep container closed.

---

## **7. HANDLING AND STORAGE**

### **Precautions for safe handling:**

Do not get on skin or in eyes. Do not inhale vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge. Open and handle container with care. Metal containers involved in the transfer of this material should be grounded and bonded.

### **Conditions for safe storage, including any incompatibilities:**

Keep container tightly closed in a cool, dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leaks/spills. Consult local fire codes for additional storage information.

---

## **8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Control parameters, e.g., occupational exposure limit values or biological limit values:**

**Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)  
+1.703.527.3887 (INT)**

**Occupational Exposure Limits**

Component	Source	Type	Value	Note
Ethyl alcohol	US (ACGIH)	STEL	1000 ppm	Upper Respiratory Tract irritation Confirmed animal carcinogen with unknown relevance to humans
Ethyl alcohol	US (OSHA)	TWA	1000 ppm / 1,900 mg/m <sup>3</sup>	29 CFR 1910.1000 Table Z-1 Limits for Air Contaminants.
Isopropyl Alcohol	US (OSHA)	STEL	500 ppm	
Isopropyl Alcohol	US (ACGIH)	TWA	200 ppm	
Isopropyl Alcohol	US (ACGIH)	STEL	400 ppm	
Methyl Isobutyl Ketone	US (ACGIH)	TWA	50 ppm	
Methyl Isobutyl Ketone	US (ACGIH)	STEL	75 ppm	

**Appropriate engineering controls:**

General room or local exhaust ventilation is usually required to meet exposure limit(s). Electrical equipment should be grounded and conform to applicable electrical code.

**Individual protection measures, such as personal protective equipment:**

**Respiratory protection:**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

**Hand protection:**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

**Eye protection:**

Use chemical safety goggles and/or a full face shield where splashing is possible. Use equipment approved by appropriate government standards, such as NIOSH (US) or EN166 (EU) Maintain eye wash fountain and quick-drench facilities in work area.

**Skin and body protection:**

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**Hygiene measures:**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance (physical state, color, etc.)</b>	Liquid. Colorless.
---	--------------------

**Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)  
+1.703.527.3887 (INT)**

Odor	Specific data not available
Odor threshold	Specific data not available
pH	Specific data not available
Freezing point	-114°C (-173°F)
Initial boiling point and boiling range	80°C (176°F)
Flash point	14°C (58°F) - closed cup
Evaporation rate	(butyl acetate = 1) 3.0 for pure 190 ethanol
Flammability (solid, gas)	Flammable
Upper / Lower flammability or explosive limits	19% (V) / 3.3% (V) - For 100% Ethyl Alcohol
Vapor pressure	41.6mmHg (5.55 kPa)
Vapor Density	1.6 (air =1)
Relative Density	6.7 lbs/gal
Solubility(ies)	Soluble
Partition coefficient n-octanol/water(ies)	Specific data not available
Auto-ignition temperature	363°C (685.4°F) - For 100% Ethyl Alcohol
Decomposition temperature	Specific data not available
Formula (ETHANOL)	C <sub>2</sub> H <sub>6</sub> O
Formula (ISOPROPYL ALCOHOL)	C <sub>3</sub> H <sub>8</sub> O
Formula (METHYL ISOBUTYL KETONE)	C <sub>6</sub> H <sub>12</sub> O
Molecular Weight (ETHANOL)	46.07 g/mol
Molecular Weight (ISOPROPYL ALCOHOL)	60.1 g/mol
Molecular Weight (METHYL ISOBUTYL KETONE)	100.16 g/mol

## 10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	Vapors may form explosive mixture with air.
Conditions to avoid (e.g., static discharge, shock or vibration)	Heat, flames, and sparks. Extreme temperatures and direct sunlight.
Incompatible materials	Strong acids, strong oxidizing agents
Hazardous decomposition products	Carbon oxides are expected to be, under fire conditions, the primary hazardous decomposition products.

## 11. TOXICOLOGICAL INFORMATION

- Ethyl Alcohol 64-17-5

### Signs and Symptoms of Exposure

Central nervous system depression, narcosis, damage to the heart. To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

### Product Summary:

Ethanol is not toxic by OSHA standards. Coingestion of sedative hypnotics or tranquilizers can increase the toxic

**Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)  
+1.703.527.3887 (INT)**

affects of ethanol. No data available to designate the product as causing specific target organ toxicity through repeated exposure. No data available to designate product as an aspiration hazard.

**Acute Toxicity:**

LC50 Inhalation	Rat	20000 ppm	10 hrs.
LC50 Oral	Rat	7060mg/Kg BWT	
LDLo Oral	Human	1400 mg/Kg BWT	

**Irritation:**

**Eyes (ETHANOL)**

Eye exposure to Ethanol generally causes transient pain, irritation, and reflex lid closure. A foreign-body sensation may persist for one to two days. Vapors produce transient stinging and tearing, but no apparent adverse effects. Transiently impaired preception of color may occur with acute ingestion or chronic alcoholism. Standard Draize eye test (rabbit) - Dose: 500 mg Reaction: Severe Dose: 500 mg/24 hrs Reaction: Mild

**Respiratory or Skin Sensitization**

No data available

**Skin**

Standard Draize skin test (rabbit) - Dose: 20 mg/24 hrs Reaction: Moderate Repeated exposure may cause skin dryness or cracking.

**Reproductive Toxicity**

Reproductive toxicity - Human - female - Oral. Effects on Newborns - measured low appgar scores and showed signs of alcohol dependence.

**Specific target organ toxicity - single exposure (Globally Harmonized System)**

Inhalation - May cause respiratory irritation. - Lungs

**Carcinogenicity**

IARC: Not classifiable as a human carcinogen.  
ACGIH: Not classifiable as a human carcinogen.  
NTP: Not classifiable as a human carcinogen.  
OSHA: Not classifiable as a human carcinogen.

Carcinogenicity - Mouse - Oral. Tumorigenic. Tumors found in liver and formation of lymphomas in blood.

**Other Hazards**

Organ	Description
Eyes	Causes irritation to the eyes. Can cause painful sensitization to light. Can cause a form of chemical conjunctivitis and cause corneal damage.
Ingestion	Can cause gastrointestinal irritation with nausea, vomiting and diarrhea. Systemic toxicity and acidosis can occur. Advanced stages can lead to respiratory failure, kidney failure, coma, and death.



**Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)  
+1.703.527.3887 (INT)**

Inhalation	Causes respiratory tract irritation. Can cause narcotic effects in high concentration. Vapors may cause dizziness or suffocation. Systemic toxicity and acidosis can occur. Advanced stages can lead to respiratory failure, kidney failure, coma, and death.
Skin	Causes moderate skin irritation. Can cause dermatitis by de-fattening the skin from prolonged or repeated contact.
Chronic	Prolonged exposure can cause liver, kidney, and heart damage. Long term exposure can cause loss of appetite, weight loss, nervousness, memory loss, mental retardation.

- Isopropyl Alcohol 67-63-0

**Product Summary:**

Long-term exposure (2 years) to Isopropyl Alcohol via inhalation at concentrations up to 5000 ppm caused no exposure related increases in tumors in animals. No data available for the teratogenicity, mutagenicity, or reproductive toxicity of this product. No data available to designate the product as causing specific target organ toxicity through repeated exposure. No data available to designate product as an aspiration hazard.

**Acute Toxicity:**

LC50 Inhalation	Rat	16,000 mg/kg	8 hours
LD50 Dermal	Rabbit	12,800 mg/kg	
LD50 Oral	Rat	5045 mg/kg	Behavioral abnormalities observed such as altered sleep time and decreased activity.

**Irritation:**

**Eyes**

Rabbit - Irritating to eyes - 24 hours

**Eyes (ISOPROPANOL)**

Mildly irritating to the eye at an airborne concentration of 400 ppm, unpleasant at 800 ppm.

**Respiratory or Skin Sensitization**

No data available

**Skin**

Rabbit- mild skin irritation

**Specific target organ toxicity - single exposure (Globally Harmonized System)**

Inhalation - May cause drowsiness or dizziness. - Central Nervous System

**Carcinogenicity**

IARC: Group 3: Not classifiable as to its carcinogenicity to humans.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)  
+1.703.527.3887 (INT)**

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**Other Hazards**

Organ	Description
Eyes	Produces irritation, characterized by a burning sensation, redness, tearing, inflammation, and possible corneal injury. May cause transient corneal injury
Ingestion	Causes gastrointestinal irritation with nausea, vomiting and diarrhea. May cause kidney damage. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure.
Inhalation	Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. May cause narcotic effects in high concentration. Causes upper respiratory tract irritation. Inhalation of vapors may cause drowsiness and dizziness. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal. The probable oral lethal dose in humans is 240 ml (2696 mg/kg), but ingestion of only 20 ml (224 mg/kg) has caused poisoning.
Skin	May cause irritation with pain and stinging, especially if the skin is abraded. Isopropanol has a low potential to cause allergic skin reactions; however, rare cases of allergic contact dermatitis have been reported. May be absorbed through intact skin. Dermal absorption has been considered toxicologically insignificant.
Chronic	Prolonged exposure can be irritating to mucous membranes, skin, and the respiratory system. Can cause liver and kidney damage.

- Methyl Isobutyl Ketone 108-10-1

**Product Summary:**

Laboratory tests have shown teratogenic effects. No data available for the mutagenic effects for this product. No data available to designate the product as causing specific target organ toxicity through single or repeated exposure. No data available to designate product as an aspiration hazard.

**Acute Toxicity:**

LC50 (Inhalation)	Rat	16.4 mg/m3	4 hours
LD50 (Dermal)	Rabbit	> 16,000 mg/kg	
LD50 (Oral)	Rat	2,080 mg/kg	

**Irritation:**

**Eyes (METHYL ISOBUTYL KETONE)**

Rabbit - Moderate eye irritation - 24 hours

**Respiratory or Skin Sensitization**

No data available

**Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)  
+1.703.527.3887 (INT)**

**Skin**

Rabbit - skin irritation - 24 hours

**Specific target organ toxicity - single exposure (Globally Harmonized System)**

Inhalation - May cause respiratory irritation. - Lungs

**Teratogenicity (METHYL ISOBUTYL KETONE)**

Methyl Isobutyl Ketone is teratogenic. Fetal death and developmental abnormalities occurred in the babies of mice that inhaled Methyl isobutyl ketone.

**Carcinogenicity**

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**Other Hazards**

Organ	Description
Eyes	Can be irritating to the eyes
Ingestion	Can be harmful if ingested.
Inhalation	Can be harmful, causing respiratory tract irritation, if inhaled.
Skin	Can be harmful, causing irritation, if absorbed through the skin.

**12. ECOLOGICAL INFORMATION**

- Ethyl Alcohol 64-17-5

**Ecotoxicity (aquatic and terrestrial, where available):**

**Acute Fish toxicity (ETHANOL)**

LC50 / 96 HOUR Oncorhynchus mykiss (rainbow trout) > 10,000 mg/l

LC50 / 96 HOUR Pimephales promelas (fathead minnow) > 13,400 mg/l

**Toxicity to aquatic plants (ETHANOL)**

Growth inhibition / 96 HOURS Chlorella vulgaris (Fresh water algae) 1,000 mg/l

**Toxicity to microorganisms (ETHANOL)**

**Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)  
+1.703.527.3887 (INT)**

Toxicity Threshold / Pseudomonas putida 6,500 mg/l  
Summary: Inhibition of cell multiplication begins.

**Persistence and degradability:**

Biodegradation is expected.

**Bioaccumulative potential:**

Biaccumulation is unlikely

**Other adverse effects:**

No data available

• Isopropyl Alcohol 67-63-0

---

**Ecotoxicity (aquatic and terrestrial, where available):**

**Acute Fish Toxicity (ISOPROPANOL)**

LC50 / 96 hours Pimephales promelas: 9,640 mg/L

**Toxic to Daphnia and Other Aquatic Invertebrates**

EC50 / 24 h / Water Flea - 5,102 mg/L

**Toxicity to Aquatic Plants (ISOPROPANOL)**

EC50 / 72 hours Desmodesmus subspicatus > 2,000 mg/L

**Toxicity to Daphnia and other aquatic invertebrates**

Immobilization EC50 / 24h / Water flea - 6,851 mg/L

**Persistence and degradability:**

No data available

**Bioaccumulative potential:**

No data available

**Other adverse effects:**

No data available

• Methyl Isobutyl Ketone 108-10-1

---

**Ecotoxicity (aquatic and terrestrial, where available):**

**Acute Toxicity to Fish (METHYL ISOBUTYL KETONE)**

LC50 / 48 hours Leuciscus idus melanotus- 480 mg/L

**Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)  
+1.703.527.3887 (INT)**

**Toxicity to Aquatic Plants (METHYL ISOBUTYL KETONE)**  
EC50 / 48 hours Green algae- 2,000 mg/L

**Persistence and degradability:**  
Biotic/ Aerobic

**Bioaccumulative potential:**  
No data available

**Other adverse effects:**  
No data available

---

### 13. DISPOSAL CONSIDERATIONS

**Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging:**

Vapors may collect in empty containers. Treat empty containers as hazardous. Dispose of spill-clean up and other wastes in accordance with Federal, State, and local regulations.

---

### 14. TRANSPORT INFORMATION

**Description of waste residues and information on their safe handling and methods of disposal:**

<b>UN number</b>	1987
<b>UN proper shipping name</b>	Alcohols, n.o.s. (Ethanol, Isopropanol)
<b>Transport hazard class(es)</b>	3
<b>Packing group (if applicable)</b>	II

**IMDG**

UN-Number: 1987 Class: 3 Packing Group: II  
EMS-No: F-E, S-D  
Proper shipping name: ALCOHOLS, N.O.S. (ETHANOL, ISOPROPANOL)  
Marine pollutant: No

**IATA**

UN-Number: 1987 Class: 3 Packing Group: II  
Proper shipping name: Alcohols, n.o.s. (Ethanol, Isopropanol)

---

### 15. REGULATORY INFORMATION

**Safety, health and environmental regulations specific for the product in question:**

**OSHA Hazards**

Flammable liquid, Target Organ Effect, Irritant

**Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)  
+1.703.527.3887 (INT)**

All ingredients are on the following inventories or are exempted from listing

Country	Notification
Australia	AICS
Canada	DSL
China	IECS
European Union	EINECS
Japan	ENCS/ISHL
Korea	ECL
New Zealand	NZIoC
Philippines	PICCS
United States of America	TSCA

#### **SARA 302 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### **SARA 313 Components**

This material does not contain any chemical components with known CAS numbers that exceed the reporting limits.

#### **SARA 311/312 Hazards**

Acute Health Hazard  
Fire Hazard

#### **CERCLA**

Methyl Isobutyl Ketone CAS-No. 108-10-1, RQ: 5,000 lbs

#### **Massachusetts Right To Know Components**

Ethanol CAS-No.64-17-5 Revision Date 2007-03-01

Isopropyl Alcohol CAS-No. 67-63-0 Revision Date 1987-01-01

Methyl Isobutyl Ketone CAS-No. 108-10-1 Revision Date 1993-04-24

#### **Pennsylvania Right To Know Components**

Ethanol CAS-No.64-17-5 Revision Date 2007-03-01

Isopropyl Alcohol CAS-No. 67-63-0 Revision Date 1987-01-01

Methyl Isobutyl Ketone CAS-No. 108-10-1 Revision Date 1993-04-24

**Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA)  
+1.703.527.3887 (INT)**

**New Jersey Right To Know Components**

Ethanol CAS-No.64-17-5 Revision Date 2007-03-01

Isopropyl Alcohol CAS-No. 67-63-0 Revision Date 1987-01-01

Methyl Isobutyl Ketone CAS-No. 108-10-1 Revision Date 1993-04-24

**California Prop 65 Components**

WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm (ETHYL ALCOHOL) CAS No. 64-17-5 Revision Date: December 11, 2009

WARNING! This product contains a chemical known to the State of California to cause cancer. METHYL ISOBUTYL KETONE CAS-No. 108-10-1 Revision Date 2011-11-04

---

## **16. OTHER INFORMATION: INCLUDING INFORMATION ON PREPARATION AND REVISION OF THE SDS**

**Disclaimer**

PHARMCO-AAPER believes that the information on this MSDS was obtained from reliable sources. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, PHARMCO-AAPER does not assume responsibility and expressly disclaims liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this MSDS information may not be applicable. Information is correct to the best of our knowledge at the date of the MSDS publication.