

+1.703.527.3887 (INT)

Distributed by:

4621 Technology Drive, Golden, CO 80403 pH: (303) 762-0800 fax: (303) 762-1240

Part #: H1032, H1034

SAFETY DATA SHEET

Heptane, n-

1. IDENTIFICATION OF SUBSTANCE / MIXTURE AND OF SUPPLIER

Product Identifier:Synonyms:
High Purity Chemicals
Heptane; Rubber solvent

Other means of identification: CAS No.142-82-5

EINECS No.205-563-8

Recommended use of the chemical and restrictions on use:

Supplier Details:

Pharmco Products, Inc. Pharmco Products, Inc.

58 Vale Road, Brookfield, 1101 Isaac Shelby Drive, Shelbyville,

CT 06804, USA.

Tel: 203.740.3471

Fax: 203.740.3481

KY 40065, USA.

Tel: 502.232.7600

Fax: 502.633.6100

CCN17213 CCN17213

Emergency Contact: CHEMTREC: 1.800.424.9300 (USA) / +1.703.527.3887 (International)

2. HAZARDS IDENTIFICATION

OSHA Hazards:

Flammable liquid, Irritant

Target Organs:

Central nervous system, Heart, Lungs

NFPA



GHS label elements, including precautionary statements

MSDS: 438 Revision Date: 02.11.13 Revision Number: 3.0 Initials: MW

Page 1 of 9



+1.703.527.3887 (INT)









Signal Word:

DANGER!

Hazard statement(s)

H225 Highly flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P273 Avoid release to the environment.

P501 Dispose of contents and container to an approved waste disposal plant.

P331 Do NOT induce vomiting.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or a doctor/

physician.

P210 Keep away from heat, sparks, open flames, and hot surfaces. No

smoking.

P280 Wear protective gloves and eye and face protection.

GHS Classification(s)

Aspiration hazard (Category 1)

Chronic aquatic toxicity (Category 1)

Flammable Liquids (Category 2)

Skin Irritation (Category 2)

Specific target organ toxicity - single exposure (Category 3)

Other hazards which do not result in classification:

Potential Health Effects:

Organ	Description	
Eyes	Causes eye irritation.	
Ingestion	May be harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and result in damage.	
Inhalation	ation May be harmful if inhaled. causes respiratory tract irritation. Drowsiness and dizziness may occur.	
Skin	May be harmful if absorbed through skin. Causes skin irritation.	

MSDS: 438 Revision Date: 02.11.13 Revision Number: 3.0 Initials: MW

Page 2 of 9



+1.703.527.3887 (INT)

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical identity: Rubber Solvent (n-Heptane)

 Common name / Synonym:
 Heptane

 CAS number:
 142-82-5

 EINECS number:
 205-563-8

 ICSC number:
 0657

 RTECS #:
 MI7700000

 UN #:
 UN1206

 EC #:
 601-008-00-2

% Weight	Material	CAS
100	n-Heptane	142-82-5

4. FIRST AID MEASURES

General advice

Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

Skin

Wash skin with soap and copious amounts of water. Seek medical attention.

Inhalation

Remove person to fresh air. If signs/symptoms continue, get medical attention. Give oxygen or artificial respiration as needed.

Eves

Flush eyes with water as a precaution.

Ingestion

DO NOT induce vomiting. If vomiting does occur, have victim lean forward to prevent aspiration. Rinse mouth with water. Seek medical attention. Never give andything my mouth to an unconcious individual.

5. FIRE FIGHTING MEASURES

Suitable (and unsuitable) extinguishing media:

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Specific hazards arising from the chemical (e.g., nature of any hazardous combustion products):

Carbon oxides, Oxides of phosphorus expected to be the primary hazardous combustion product.

Special protective equipment and precautions for firefighters:

Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Keep

MSDS: 438 Revision Date: 02.11.13 Revision Number: 3.0 Initials: MW



+1.703.527.3887 (INT)

unopened containers cool by spraying with water.

Flammable Properties
Flash point
-4 °C (25°F) - Closed Cup
Autoignition temperature
204°C (399 °F)

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Wear respiratory protection. Do not inhale vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions:

Stop leak / contain spill if possible and safe to do so. Prevent product from entering drains.

Methods and materials for containment and cleaning up:

Contain spill, then collect with an electrically protected vacuum cleaner or by wet-brushing and put the material into a convenient waste disposal container. Keep container closed.

7. HANDLING AND STORAGE

Precautions for safe handling:

Do not get on skin or in eyes. Do not inhale vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge. Open and handle container with care. Metal containers involved in the transfer of this material should be grounded and bonded.

Conditions for safe storage, including any incompatibilites:

Keep container tightly closed in a dry and well-ventilated place. Store under inert gas. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters, e.g., occupational exposure limit values or biological limit values:

Occupational Exposure Limits

- Companional Exposure Elimite				
Component	Source	Type	Value	Note
Heptane	US (OSHA)		500ppm, 2000 mg/m3	29 CF 1910.1000 Table Z-1 Limits for air
			300ppm, 2000 mg/m3	contaminants
n Hontono	TIC (OCHV)	T\\\\	500 nnm 2 000 mg/kg	29 CFR 1910.1000 Table Z-1 Limits for Air
n-Heptane	US (USHA) 11	IVVA	500 ppm, 2,000 mg/kg	Contaminants

MSDS: 438 Revision Date: 02.11.13 Revision Number: 3.0 Initials: MW



+1.703.527.3887 (INT)

Appropriate engineering controls:

General room or local exhaust ventilation is usually required to meet exposure limit(s). Electrical equipment should be grounded and conform to applicable electrical code.

Individual protection measures, such as personal protective equipment:

Respiratory protection:

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection:

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Eye protection:

Use chemical safety goggles and/or a full face shield where splashing is possible. Use equipment approved by appropriate government standards, such as NIOSH (US) or EN166 (EU) Maintain eye wash fountain and quick-drench facilities in work area.

Skin and body protection:

Wear impervious, flame retardant, antistatic protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.)	Liquid.
Odor	Hydrocarbon Odor
Freezing point	-91 °C (-132 °F)
Initial boiling point and boiling range	98 °C (208 °F)
Flash point	-4 °C (25°F) - Closed Cup
Flammability (solid, gas)	Flammable
Upper / Lower flammability or explosive limits	1.05% (V) 6.7% (V)
Vapor pressure	110.7 hPa (83.0 mmHg) at 37.7 °C (99.9 °F)
Vapor Density	3.5
Relative Density	0.684 g/mL at 25 °C (77 °F)
Solubility(ies)	insoluble
Partition coefficient n-octanol/water(ies)	log Pow: > 3.00
Auto-ignition temperature	204°C (339 °F)

MSDS: 438 Revision Date: 02.11.13 Revision Number: 3.0 Initials: MW

Page 5 of 9



Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA) +1.703.527.3887 (INT)

Molecullar Formula (N-HEPTANE)	C7H16
Molecular Weight (N-HEPTANE)	100.20 g/mol

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	Vapors may form explosive mixture with air.
Conditions to avoid (e.g., static discharge,	Heat, flames and sparks. Extreme temperatures and direct
shock or vibration)	sunlight.
Incompatible materials	Strong oxidizing agents
Hazardous decomposition products	Hazardous decomposition products formed under fire
nazardous decomposition products	conditions Carbon oxides

11. TOXICOLOGICAL INFORMATION

• Heptane, n- 142-82-5

Product Summary:

No data available for teratogenic, reproductive or mutagenic effects of this product.

Acute Toxicity:

LD50 (Inhalation)	Rat	103,000mg/m3	4 h

Aspiration Hazard

May be fatal if ingested or inhaled.

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Other Hazards

Organ	Description
Eyes	Causes eye irritation.
Ingestion	May be harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and result in damage.
Inhalation	May be harmful if inhaled, causes respiratory tract irritation. Drowsiness and dizziness may occur.

MSDS: 438 Revision Date: 02.11.13 Revision Number: 3.0 Initials: MW

Page 6 of 9



+1.703.527.3887 (INT)

Skin May be harmful if absorbed through skin. Causes skin irritation.

12. ECOLOGICAL INFORMATION

• Heptane, n- 142-82-5

Ecotoxicity (aquatic and terrestrial, where available):

Acute aquatic invertebrate toxicity (N-HEPTANE)

EC50 / 48 hours / Water Flea - 1.50 mg/l

Acute fish toxicity (N-HEPTANE)

LC50 / 24 hours / Goldfish - 4 mg/l

Acute toxicity to daphnia (N-HEPTANE)

EC50 / 96 hours / Mossambique Tilapia - 375 mg/l

Bioaccumulative potential:

Bioaccumulation possible.

Other adverse effects:

Possible environmental hazard if handled or disposed of improperly. Toxic to aquatic life ad environment.

13. DISPOSAL CONSIDERATIONS

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging:

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

14. TRANSPORT INFORMATION

Description of waste residues and information on their safe handling and methods of disposal:

	
UN number	UN1206
UN proper shipping name	Heptanes
Transport hazard class(es)	3
Packing group (if applicable)	II

IMDG

UN-Number: UN1206 Class: 3 Packing Group: II

MSDS: 438 Revision Date: 02.11.13 Revision Number: 3.0 Initials: MW

Page 7 of 9



+1.703.527.3887 (INT)

EMS-No: F-E, S-D

Proper shipping name: HEPTANES

Marine pollutant: No

IATA

UN-Number: UN1206 Class: 3 Packing Group: II

Proper shipping name: Heptanes

15. REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product in question:

OSHA Hazards

Flammable liquid, Irritant

All ingredients are on the following inventories or are exempted from listing

Country	Notification
Australia	AICS
Canada	DSL
China	IECS
European Union	EINECS
Japan	ENCS/ISHL
Korea	ECL
New Zealand	NZIoC
Philippines	PICCS
United States of America	TSCA

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Acute Health Hazard Fire Hazard

Massachusetts Right To Know Components

Heptane CAS-No. 142-82-5 Revision Date 1993-04-24

Pennsylvania Right To Know Components

Heptane CAS-No. 142-82-5 Revision Date 1993-04-24

MSDS: 438 Revision Date: 02.11.13 Revision Number: 3.0 Initials: MW

Page 8 of 9



+1.703.527.3887 (INT)

New Jersey Right To Know Components

Heptane CAS-No. 142-82-5 Revision Date 1993-04-24

California Prop 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION: INCLUDING INFORMATION ON PREPARATION AND REVISION OF THE SDS

Disclaimer

PHARMCO-AAPER believes that the information on this MSDS was obtained from reliable sources. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, PHARMCO-AAPER does not assume responsibility and expressly disclaims liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this MSDS information may not be applicable. Information is correct to the best of our knowledge at the date of the MSDS publication.

MSDS: 438 Revision Date: 02.11.13 Revision Number: 3.0 Initials: MW