

+1.703.527.3887 (INT)

Distributed by:

**Rocky Mountain Reagents** 

4621 Technology Drive, Golden, CO 80403 pH: (303) 762-0800 fax: (303) 762-1240

Part #'s: H1033, H1036

## SAFETY DATA SHEET

n-Hexane, 95% min

This MSDS is valid for all grades and catalog #'s

### 1. IDENTIFICATION OF SUBSTANCE / MIXTURE AND OF SUPPLIER

**Product Identifier:** High Purity Chemicals

Synonyms: n-Hexane; Hexanes, Normal Hexane; Hexyl Hydride; 3-Methyl Pentane

Other means of identification: CAS No. 110-54-3

EINECS No. 203-777-6

Recommended use of the chemical and restrictions on use:

General reagent use.

**Supplier Details:** 

Pharmco Products, Inc. Pharmco Products, Inc.

58 Vale Road, Brookfield, 1101 Isaac Shelby Drive, Shelbyville,

CT 06804, USA.

Tel: 203.740.3471

Fax: 203.740.3481

KY 40065, USA.

Tel: 502.232.7600

Fax: 502.633.6100

CCN17213 CCN17213

Emergency Contact: CHEMTREC: 1.800.424.9300 (USA) / +1.703.527.3887 (International)

### 2. HAZARDS IDENTIFICATION

#### **Emergency Overview:**

EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. HARMFUL OR FATAL IF SWALLOWED. HARMFUL IF INHALED OR ABSORBED THROUGH SKIN. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. AFFECTS THE CENTRAL AND PERIPHERAL NERVOUS SYSTEMS.

#### **OSHA Hazards:**

Flammable liquid, Irritant, Target organ effect, Teratogen

### **Target Organs:**

Kidney, Peripheral nervous system, Testes


MSDS: 942 Revision Date: 07.01.14 Revision Number: 3.1 Initials: MW

Page 1 of 11



+1.703.527.3887 (INT)

### **NFPA**



### GHS label elements, including precautionary statements









### **Signal Word:**

DANGER!

#### **Hazard statement(s)**

H225 Highly flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

### Precautionary statement(s)

P261 Avoid breathing dust/fumes/gas/mist/vapors.

P280 Wear protective gloves and eye and face protection.

P264 Wash hands thoroughly after handling.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or a doctor/

physician.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P303 + P361 + P353 IF ON SKIN (or hair): Remove immediately all contaminated clothing.

Rinse skin with water.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position

MSDS: 942 Revision Date: 07.01.14 Revision Number: 3.1 Initials: MW



+1.703.527.3887 (INT)

comfortable for breathing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P242 Use only non-sparking tools.

P202 Do not handle until all safety precautions have been read and

understood.

P210 Keep away from heat, sparks, open flames, and hot surfaces. No

smoking.

P501 Dispose of contents and container to an approved waste disposal plant.

P240 Ground/bond container and receiving equipment.
P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for

extinction.

P241 Use explosion-proof electrical, ventilating, and lighting equipment.

P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

### **GHS Classification(s)**

Aspiration hazard (Category 1)

Chronic aquatic toxicity (Category 2)

Flammable Liquids (Category 2)

Reproductive toxicity (Category 2)

Skin irritation (Category 2)

Specific target organ toxicity - repeated exposure (Category 2) Specific target organ toxicity - single exposure (Category 3)

### Other hazards which do not result in classification:

#### **Potential Health Effects:**

Organ	Description
Eyes	Can be irritating to the eyes.
Ingestion	Can be harmful if ingested. Aspiration hazard if swallowed - can enter lungs and cause damage.
Inhalation	May cause irritation to the respiratory tract if inhaled. Vapors can cause drowsiness and dizziness.
Skin	May cause skin irritation if product is absorbed through the skin.

### 3. COMPOSITION AND INFORMATION ON INGREDIENTS

**Chemical identity:** n-Hexane, 95% min

**Common name / Synonym:** n-Hexane; Hexanes, Normal Hexane; Hexyl Hydride; 3-Methyl Pentane

 CAS number:
 110-54-3

 EINECS number:
 203-777-6

 ICSC number:
 0279

MSDS: 942 Revision Date: 07.01.14 Revision Number: 3.1 Initials: MW

Page 3 of 11



+1.703.527.3887 (INT)

RTECS #: MN9275000

**UN #**: 1208

**EC #**: 601-037-00-0

% Weight	Material	CAS
≥ 95	n-Hexane	110-54-3

### 4. FIRST AID MEASURES

### General advice

Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### Skin

Wash skin with soap and copious amounts of water. Seek medical attention.

#### Inhalation

Remove person to fresh air. If signs/symptoms continue, get medical attention. Give oxygen or artificial respiration as needed.

#### **Eves**

Thoroughly flush the eyes with large amounts of clean low-pressure water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If irritation persists, seek medical attention.

### Ingestion

DO NOT induce vomiting. If vomiting does occur, have victim lean forward to prevent aspiration. Rinse mouth with water. Seek medical attention. Never give anything by mouth to an unconscious individual.

### 5. FIRE FIGHTING MEASURES

### Suitable (and unsuitable) extinguishing media:

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

### Specific hazards arising from the chemical (e.g., nature of any hazardous combustion products):

Carbon oxides expected to be the primary hazardous combustion product.

### Special protective equipment and precautions for firefighters:

Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Keep unopened containers cool by spraying with water.

#### Flammable Properties

Classification

OSHA/NFPA Class IB Flammable Liquid.

Flash point

MSDS: 942 Revision Date: 07.01.14 Revision Number: 3.1 Initials: MW



+1.703.527.3887 (INT)

-22 °C (-7 °F) - closed cup **Autoignition temperature** 225 °C (437 °F)

### 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures:

Wear respiratory protection. Do not inhale vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

#### **Environmental precautions:**

Stop leak. Contain spill if possible and safe to do so. Prevent product from entering drains.

### Methods and materials for containment and cleaning up:

Contain spill, then collect with an electrically protected vacuum cleaner or by wet-brushing and put the material into a convenient waste disposal container. Keep container closed.

### 7. HANDLING AND STORAGE

#### Precautions for safe handling:

Do not get on skin or in eyes. Do not inhale vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge.

### Conditions for safe storage, including any incompatibilites:

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters, e.g., occupational exposure limit values or biological limit values:

#### **Occupational Exposure Limits**

Component	Source	Type	Value	Note
n-Hexane	US (OSHA)	TWA	500 ppm, 1800 mg/m3	29 CFR 1910.1000 Table Z-1 Limits for Air Contaminants

#### Appropriate engineering controls:

General room or local exhaust ventilation is usually required to meet exposure limit(s). Electrical equipment should be grounded and conform to applicable electrical code.

### Individual protection measures, such as personal protective equipment:

Respiratory protection:

MSDS: 942 Revision Date: 07.01.14 Revision Number: 3.1 Initials: MW

Page 5 of 11



# Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA) +1.703.527.3887 (INT)

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Hand protection:

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

### Eye protection:

Use chemical safety goggles and/or a full face shield where splashing is possible. Use equipment approved by appropriate government standards, such as NIOSH (US) or EN166 (EU) Maintain eye wash fountain and quick-drench facilities in work area.

### Skin and body protection:

Wear impervious, flame retardant, antistatic protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

### Hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

on the diameter in the entire	_0
Appearance (physical state, color, etc.)	Liquid. Colorless.
Odor	Specific data not available
Odor threshold	Specific data not available
рН	Specific data not available
Freezing point	-95 °C (-139 °F)
Initial boiling point and boiling range	69 °C (156 °F)
Flash point	-22 °C (-7 °F) - closed cup
Evaporation rate	Specific data not available
Flammability (solid, gas)	Flammable
Upper / Lower flammability or explosive limits	7.7% (V) / 1.2% (V)
Vapor pressure	176.0 hPa (132.0 mmHg) at 20 °C (68 °F)
Vapor Density	3.0
Relative Density	0.659 g/mL at 25 °C (77 °F)
Solubility(ies)	not soluble
Partition coefficient n-octanol/water(ies)	log Pow: 4
Auto-ignition temperature	225 °C (437 °F)
Decomposition temperature	Specific data not available
Formula (N-HEXANE)	C6H14
Molecular Weight (N-HEXANE)	86.18 g/mol

MSDS: 942 Revision Date: 07.01.14 Revision Number: 3.1 Initials: MW

Page 6 of 11



+1.703.527.3887 (INT)

### 10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended storage conditions.	
Possibility of hazardous reactions	Vapors may form explosive mixture with air.	
Conditions to avoid (e.g., static discharge,	Heat, flames, and sparks. Extreme temperatures and direct	
shock or vibration)	sunlight.	
Incompatible materials	Strong oxidizing agents	
Hazardous decomposition products	Carbon oxides are expected to be, under fire conditions, the	
Hazardous decomposition products	primary hazardous decomposition products.	

### 11. TOXICOLOGICAL INFORMATION

#### • n-Hexane 110-54-3

### **Product Summary:**

Laboratory tests have shown reproductive effects in animals. Product is damaging to human fertility. No data available for the teratogenic or mutagenic effects of the product.

### **Acute Toxicity:**

LC50 (Inhalation)	Rat	48,000 ppm	4 hours
LD50 (Oral)	Rat	25,000 mg/kg	

### Irritation:

#### **Eyes**

Rabbit - mild eye irritation

### **Respiratory or Skin Sensitization**

No data available

### Skin

No data available

### **Aspiration Hazard**

May be fatal if ingested or inhaled.

### Reproductive toxicity

Presumed human reproductive toxicant

### Specific target organ toxicity - repeated exposure (Globally Harmonized System)

May cause damage to organs through prolonged or repeated exposure. Route: Inhalation. Organs: Nervous System

MSDS: 942 Revision Date: 07.01.14 Revision Number: 3.1 Initials: MW



+1.703.527.3887 (INT)

### Specific target organ toxicity - single exposure (Globally Harmonized System)

Inhalation - May cause respiratory irritation - Respiratory tract

### Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Carcinogenicity - Rat. Route: Inhalation. Development of testicular tumors.

#### Other Hazards

Organ	Description
Eyes	Irritating to the eyes.
Ingestion	Can be harmful if swallowed. Aspiration hazard if swallowed - can enter lungs and cause damage.
Inhalation	Can be harmful if inhaled. Irritating to the respiratory tract. Vapors can cause drowsiness and dizziness.
Skin	Can be harmful if absorbed through skin. Irritating to the skin.

### 12. ECOLOGICAL INFORMATION

• n-Hexane 110-54-3

Ecotoxicity (aquatic and terrestrial, where available):

**Acute Fish Toxicity (N-HEXANE)** 

LC50 / 96 hours Fathead Minnow - 2.5 mg/L

**Toxicity to Daphnia (N-HEXANE)** 

EC50 / 48 hours Water flea - 3,878 mg/L

Persistence and degradability:

No data available

Bioaccumulative potential:

No data available

MSDS: 942 Revision Date: 07.01.14 Revision Number: 3.1 Initials: MW

Page 8 of 11



+1.703.527.3887 (INT)

### Other adverse effects:

Product can be considered an environmental hazard if handled improperly or through improper disposal.

### 13. DISPOSAL CONSIDERATIONS

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging:

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved incinerator or disposed in RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. Refer to applicable regional, state and federal codes.

### 14. TRANSPORT INFORMATION

Description of waste residues and information on their safe handling and methods of disposal:

UN number	1208
UN proper shipping name	Hexanes
Transport hazard class(es)	3
Packing group (if applicable)	II

### Reportable Quantity

5,000 lbs **IMDG** 

UN-Number: 1208 Class: 3 Packing Group: II

EMS-No: F-E, S-D

Proper shipping name: HEXANES

Marine pollutant: No

**IATA** 

UN-Number: 1208 Class: 3 Packing Group: II

Proper shipping name: Hexanes

### 15. REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product in question:

### **OSHA Hazards**

Flammable liquid, Irritant, Target organ effect, Teratogen

All ingredients are on the following inventories or are exempted from listing

Country	Notification
Australia	AICS
Canada	DSL
China	IECS

MSDS: 942 Revision Date: 07.01.14 Revision Number: 3.1 Initials: MW

Page 9 of 11



+1.703.527.3887 (INT)

European Union	EINECS
Japan	ENCS/ISHL
Korea	ECL
New Zealand	NZIoC
Philippines	PICCS
United States of America	TSCA

### **SARA 302 Components**

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

### **SARA 313 Components**

The following components are subject to reporting levels established by SARA Title III, Section 313: N-HEXANE CAS-No. 110-54-3 Revision Date 2007-07-01

### SARA 311/312 Hazards

Acute Health Hazard Chronic Health Hazard Fire Hazard

#### **CERCLA**

Hexane CAS-No. 110-54-3, RQ: 5,000 lbs

### **Massachusetts Right To Know Components**

n-Hexane CAS-No. 110-54-3 Revision Date 2007-07-01

### Pennsylvania Right To Know Components

n-Hexane CAS-No. 110-54-3 Revision Date 2007-07-01

### **New Jersey Right To Know Components**

n-Hexane CAS-No. 110-54-3 Revision Date 2007-07-01

### **California Prop 65 Components**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

### **16. OTHER INFORMATION:**

### INCLUDING INFORMATION ON PREPARATION AND REVISION OF THE SDS

MSDS: 942 Revision Date: 07.01.14 Revision Number: 3.1 Initials: MW

Page 10 of 11



Product Information: 203.740.3471 Emergency Assistance (CHEMTREC): 1.800.424.9300 (USA) +1.703.527.3887 (INT)

### **Disclaimer**

PHARMCO-AAPER believes that the information on this MSDS was obtained from reliable sources. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, PHARMCO-AAPER does not assume responsibility and expressly disclaims liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this MSDS information may not be applicable. Information is correct to the best of our knowledge at the date of the MSDS publication.

MSDS: 942 Revision Date: 07.01.14 Revision Number: 3.1 Initials: MW

Page 11 of 11