

Revision Date: 10-27-2015

Distributed by:

4621 Technology Drive, Golden, CO 80403 ph: (303) 762-0800 fax: (303) 762-1240

SAFETY DATA SHEET

1. Identification

Product identifier: Isopropyl Alcohol

Other means of identification

Synonyms: 2-Propanol, Dimethyl carbinol, sec-Propyl alcohol

Product No.: 3591, 3593, 3590, V566, V555, 9080, 9037, 3043, 3031, U298, 9084,

H604, 3032, 0562

Recommended use and restriction on use

Recommended use: Not available.
Restrictions on use: Not known.

Details of the supplier of the safety data sheet

Manufacturer

Company Name: Avantor Performance Materials, Inc.

Address: 3477 Corporate Parkway, Suite 200

Center Valley, PA 18034

Telephone: Customer Service: 855-282-6867

Fax: 610-573-2610

Contact Person: Environmental Health & Safety E-mail: info@avantormaterials.com

Emergency telephone number:

CHEMTREC: 1-800-424-9300 within US and Canada CHEMTREC: 1-703-527-3887 outside US and Canada

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids Category 2

Health Hazards

Serious Eye Damage/Eye Irritation Category 2A
Specific Target Organ Toxicity - Category 3

Single Exposure

Label Elements

Hazard Symbol:



Signal Word: Danger



Revision Date: 10-27-2015

Hazard Statement: Highly flammable liquid and vapor.

Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary Statement

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Keep container tightly closed. Ground and bond

container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. Wash hands thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. In case of fire: Use

water spray, foam, dry powder or carbon dioxide for extinction.

Storage: Store in a well-ventilated place. Keep cool. Keep container tightly closed.

Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

None.

3. Composition/information on ingredients

Substances

Chemical Identity	Common name and synonyms	CAS number	Content in percent (%)*	
ISOPROPYL ALCOHOL		67-63-0	98 - 100%	

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

General information: Get medical advice/attention if you feel unwell. Show this safety data sheet

to the doctor in attendance.

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Do

NOT induce vomiting. If vomiting occurs, keep head low so that stomach

content doesn't get into the lungs.

Inhalation: Move to fresh air. Get medical attention if symptoms persist.

Skin Contact: Wash skin thoroughly with soap and water. Get medical attention if

symptoms occur. Remove contaminated clothing and shoes. Wash

contaminated clothing before reuse.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Get medical attention.



Revision Date: 10-27-2015

Most important symptoms/effects, acute and delayed

Symptoms: Irritating to eyes, respiratory system and skin.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed. Treat symptomatically.

5. Fire-fighting measures

General Fire Hazards: Flammable liquid and vapor.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Water spray, foam, dry powder or carbon dioxide.

Unsuitable extinguishing

media:

Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from

the chemical:

Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations. Vapor from the solvent may accumulate in container headspace resulting in flammability hazard. Heat may cause the containers to explode.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move

containers from fire area if you can do so without risk.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Avoid breathing mists or vapors. Keep upwind. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. See Section 8 of the SDS for Personal Protective Equipment. Keep unauthorized

personnel away.

Methods and material for containment and cleaning up:

Eliminate all ignition sources if safe to do so. Use only non-sparking tools. Take precautionary measures against static discharges. Stop leak if possible without any risk. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination. Dike far ahead of larger spill

for later recovery and disposal.

Notification Procedures: Prevent entry into waterways, sewer, basements or confined areas. Inform

authorities if large amounts are involved.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so.



Revision Date: 10-27-2015

7. Handling and storage

Precautions for safe handling:

Do not handle until all safety precautions have been read and understood. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Take precautionary measures against static discharges. Ground and bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting/equipment. Use only non-sparking tools. Wear protective gloves/protective clothing/eye protection/face protection. Avoid contact with eyes, skin, and clothing. Do not breathe mist or vapor. Use only with adequate ventilation. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Keep away from food, drink and animal feeding stuffs. Keep container tightly closed in a cool, well-ventilated place. Ground container and transfer equipment to eliminate static electric sparks. Comply with all national, state, and local codes pertaining to the storage, handling, dispensing, and disposal of flammable liquids.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Value	es	Source
ISOPROPYL ALCOHOL	TWA	200 ppm		US. ACGIH Threshold Limit Values (2011)
	STEL	400 ppm		US. ACGIH Threshold Limit Values (2011)
	REL	400 ppm 980 m	ng/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	500 ppm 1,225 m	ng/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	PEL	400 ppm 980 m	ng/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	400 ppm 980 m	ng/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	500 ppm 1,225 m	ng/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)

Biological Limit Values

-	2101091041 2111111 141400							
	Chemical Identity	Exposure Limit Values	Source					
	ISOPROPYL ALCOHOL (acetone: Sampling time: End	40 mg/l (Urine)	ACGIH BEL (03 2013)					
	of shift at end of work week.)							

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

General information: Good general ventilation (typically 10 air changes per hour) should be used.

Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If

exposure limits have not been established, maintain airborne levels to an acceptable level. An eye wash and safety shower must be available in the

immediate work area. Use explosion-proof ventilation equipment.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Chemical resistant gloves

Other: Wear suitable protective clothing and gloves.



Revision Date: 10-27-2015

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Chemical

respirator with organic vapor cartridge.

Hygiene measures: Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Provide eyewash station and safety shower. Avoid contact with eyes, skin,

and clothing.

9. Physical and chemical properties

Appearance

Physical state: liquid
Form: liquid
Color: Colorless

Odor: Odor of rubbing alcohol
Odor threshold: No data available.
pH: No data available.

Melting point/freezing point: -88.5 °C

Initial boiling point and boiling range:

82 °C (101.3 kPa)

12 °C (Closed Cup)

Evaporation rate:

2.8 n-butyl acetate=1

Flammability (solid, gas):

Class IB Flammable Liquid

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): 12 %(V)
Flammability limit - lower (%): 2.5 %(V)

Explosive limit - upper (%):

Explosive limit - lower (%):

Vapor pressure:

Vapor density:

Relative density:

No data available.

0.0 kPa (25 °C)

2.1 AIR=1

0.7850 (4 °C)

Solubility(ies)

Solubility in water: Miscible with water.
Solubility (other): No data available.

Partition coefficient (n-octanol/water): 0.05
Auto-ignition temperature: 399 °C

Decomposition temperature:No data available. **Viscosity:**No data available.

Other information

Molecular weight: 60.1 g/mol (C3H8O)

10. Stability and reactivity

Reactivity: No dangerous reaction known under conditions of normal use.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

Hazardous polymerization does not occur.

Conditions to avoid: Heat, sparks, flames. Sunlight.



Revision Date: 10-27-2015

Incompatible Materials: Strong oxidizing agents. Acetaldehyde. Acids. Chlorine. Ethylene Oxide

Hydrogen peroxide (H2O2) Sulfuric acid. Isocyanates. Aluminum.

Hazardous Decomposition

Products:

Thermal decomposition may release oxides of carbon.

11. Toxicological information

Information on likely routes of exposure

Ingestion: Irritating. May cause nausea, stomach pain and vomiting.

Inhalation: May cause irritation to the mucous membranes and upper respiratory tract.

May cause central nervous system effects.

Skin Contact: Causes mild skin irritation.

Eye contact: Causes serious eye irritation.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: LD 50 (Rat): 5,045 mg/kg

Dermal

Product: LD 50 (Rabbit): 12,800 mg/kg

Inhalation

Product: No data available.

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: Prolonged or repeated skin contact may cause drying, cracking, or irritation.

Serious Eye Damage/Eye Irritation

Product: Irritating to eyes.

Respiratory or Skin Sensitization

Product: Not a skin sensitizer.

Carcinogenicity

Product: This substance has no evidence of carcinogenic properties.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.



Revision Date: 10-27-2015

Reproductive toxicity

Product: No components toxic to reproduction

Specific Target Organ Toxicity - Single Exposure

Product: Central nervous system. - Narcotic effect.

Specific Target Organ Toxicity - Repeated Exposure

Product: None known.

Aspiration Hazard

Product: May be harmful if swallowed and enters airways.

Other effects: None known.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: LC 50 (Western mosquitofish (Gambusia affinis), 96 h): > 1,400 mg/l

Aquatic Invertebrates

Product: LC 50 (Water flea (Daphnia magna), 24 h): 10,000 mg/l

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: Expected to be readily biodegradable.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available on bioaccumulation.

Partition Coefficient n-octanol / water (log Kow)
Product: Log Kow: 0.05

Mobility in Soil: The product is partly soluble in water. May spread in the aquatic

environment.

Other Adverse Effects: The product components are not classified as environmentally hazardous.

However, this does not exclude the possibility that large or frequent spills

can have a harmful or damaging effect on the environment.



Revision Date: 10-27-2015

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local

laws. Disposal recommendations are based on uncontaminated material.

Contaminated Packaging: Since emptied containers retain product residue, follow label warnings even

after container is emptied.

14. Transport information

DOT

UN Number: UN 1219 UN Proper Shipping Name: Isopropanol

Transport Hazard Class(es)

Class(es): 3
Label(s): 3
Packing Group: II

Marine Pollutant: Not a Marine Pollutant

Special precautions for user: -

IMDG

UN Number: UN 1219
UN Proper Shipping Name: ISOPROPANOL

Transport Hazard Class(es)

 Class(es):
 3

 Label(s):
 3

 EmS No.:
 F-E, S-D

Packing Group:

Marine Pollutant: Not a Marine Pollutant

Special precautions for user: -

IATA

UN Number: UN 1219
Proper Shipping Name: Isopropanol

Transport Hazard Class(es):

Class(es): 3 Label(s): 3

Marine Pollutant: Not a Marine Pollutant

Packing Group: II Special precautions for user: –

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u> <u>Reportable quantity</u>

ISOPROPYL ALCOHOL 100 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Acute (Immediate)

Fire

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.



Revision Date: 10-27-2015

SARA 304 Emergency Release Notification

Reportable quantity **Chemical Identity**

ISOPROPYL ALCOHOL 100 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity Threshold Planning Quantity

ISOPROPYL ALCOHOL 10000 lbs

SARA 313 (TRI Reporting)

Reporting Reporting threshold for threshold for manufacturing and

other users processing

Chemical Identity ISOPROPYL ALCOHOL 10000 lbs 25000 lbs.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

No ingredient regulated by CA Prop 65 present.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

ISOPROPYL ALCOHOL

US. Massachusetts RTK - Substance List

Chemical Identity

ISOPROPYL ALCOHOL

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

ISOPROPYL ALCOHOL

US. Rhode Island RTK

Chemical Identity

ISOPROPYL ALCOHOL

Inventory Status:


Australia AICS: On or in compliance with the inventory Canada DSL Inventory List: On or in compliance with the inventory EINECS, ELINCS or NLP: On or in compliance with the inventory On or in compliance with the inventory Japan (ENCS) List: China Inv. Existing Chemical Substances: Not in compliance with the inventory. Korea Existing Chemicals Inv. (KECI): On or in compliance with the inventory Canada NDSL Inventory: Not in compliance with the inventory. Philippines PICCS: On or in compliance with the inventory US TSCA Inventory: On or in compliance with the inventory New Zealand Inventory of Chemicals: On or in compliance with the inventory Japan ISHL Listing: On or in compliance with the inventory Not in compliance with the inventory. Japan Pharmacopoeia Listing:

16.Other information, including date of preparation or last revision



Revision Date: 10-27-2015

NFPA Hazard ID



Hazard rating: 0 - Minimal; 1 - Slight; 2 Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible

Issue Date: 10-27-2015

Revision Date: No data available.

Version #: 1.1

Further Information: No data available.

Disclaimer: THE INFORMATION PRESENTED IN THIS MATERIAL SAFETY DATA

SHEET (MSDS/SDS) WAS PREPARED BY TECHNICAL PERSONNEL BASED ON DATA THAT THEY BELIEVE IN THEIR GOOD FAITH

JUDGMENT IS ACCURATE. HOWEVER, THE INFORMATION PROVIDED

HEREIN IS PROVIDED "AS IS," AND AVANTOR PERFORMANCE MATERIALS MAKES AND GIVES NO REPRESENTATIONS OR WARRANTIES WHATSOEVER, AND EXPRESSLY DISCLAIMS ALL

WARRANTIES REGARDING SUCH INFORMATION AND THE PRODUCT TO WHICH IT RELATES, WHETHER EXPRESS, IMPLIED, OR

STATUTORY, INCLUDING WITHOUT LIMITATION, WARRANTIES OF

ACCURACY, COMPLETENESS, MERCHANTABILITY, NON-

INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY, STABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, AND ANY WARRANTIES ARISING FROM COURSE OF DEALING, COURSE OF PERFORMANCE, OR USAGE OF TRADE. THIS MSDS/SDS IS INTENDED ONLY AS A GUIDE TO THE APPROPRIATE PRECAUTIONARY HANDLING OF THE MATERIAL BY A PROPERLY TRAINED PERSON USING THIS PRODUCT, AND IS NOT INTENDED TO BE COMPREHENSIVE AS TO THE MANNER AND CONDITIONS OF USE, HANDLING, STORAGE, OR DISPOSAL OF THE PRODUCT. INDIVIDUALS RECEIVING THIS MSDS/SDS MUST

ALWAYS EXERCISE THEIR OWN INDEPENDENT JUDGMENT IN DETERMINING THE APPROPRIATENESS OF SUCH ISSUES.

ACCORDINGLY, AVANTOR PERFORMANCE MATERIALS ASSUMES NO LIABILITY WHATSOEVER FOR THE USE OF OR RELIANCE UPON THIS INFORMATION. NO SUGGESTIONS FOR USE ARE INTENDED AS, AND NOTHING HEREIN SHALL BE CONSTRUED AS, A RECOMMENDATION TO INFRINGE ANY EXISTING PATENTS OR TO VIOLATE ANY FEDERAL, STATE, LOCAL, OR FOREIGN LAWS. AVANTOR PERFORMANCE

MATERIALS REMINDS YOU THAT IT IS YOUR LEGAL DUTY TO MAKE ALL INFORMATION IN THIS MSDS/SDS AVAILABLE TO YOUR

EMPLOYEES.